Lighting Specification Sheet

Classic Wall Wash (CWW1CB)



Old world craftsmanship. . .tomorrow's technology®

_ Date: _____ Project: _____ Fixture Type: _____ Quantity: _____ Specifier: Drawing not to scale Must operate lamp between 9 to 20 volts. 5-3/8" molded convex pyrex glass lens. -Check voltage with digital multi-meter. Extremely durable solid sand cast 88-6-3-2 bronze body. Soldered, crimped and heat-shrunk electrical connection to lead wire. 5.5" Heavy duty 100% solid copper fixture stem - .115 wall thickness. 304 knurled & slotted easy grip thumb screws. Keep stake top flush w/grade. Install at 90° Compact backfill in 4" lifts. to grade. Extremely durable solid bronze stake. #16-2@25' Tin coated marine grade No-Ox® wire. Bury wire at 6" depth. Coil leftover wire at base of fixture. This allows for future field adjustment of fixture placement if required. Plan Symbol: Notes -

CWW1CB: Includes 2.5W S8 LED Lamp (SL3156250L) Max. lamp rating 35 watts

MOUNTING OPTIONS

- Mounting Canopy Unthreaded (CFM1CBS)
- Standard Mounting Stake (CMS1CB) included
- Standard Mounting Stake (CLMS1CB)
- Heavy Duty Mounting Stake (CHMS1CB)

*NOTE: This is a threaded stake. To use with this fixture, purchase adapter (XCBPTLTA)

Unthreaded Stems:

- Replacement Stem (XCBPSTEMS_____)
- Telescopic Stem (CWTRS_____)