Lighting Specification Sheet

Classic Small China Hat Canopy Mount Area/Path Light (CCH13CB)



Old world craftsmanship. . .tomorrow's technology *

Project:		Date:	
•	Quantity:		
Drawing not to scale			
LED Retrofit: use CALED2- replaces halogen lamp	CCH13CB: Must operate lampa-12.0 volts AC. Optimal range Check voltage with digital must be surface paint. Reflected "no glare" light source. CCH13CB: Wedge-base 25 watt Krypton lamp light source. CCH13LED1A: Amber CAST Dynasty 1156 LED (Turtle-Safe) CCH13LED1R: Red CAST Dynasty 1156 LED (Turtle-Safe) #16-2@25' Tin coated marine grade No-Ox® wire. Bury wire at 6" depth.	is 10.8 to 11.324.0 volts AC digital multi-meter. Soldere electrice by the second	304 knurled & slotted easy grip thumb screws. Extremely durable solid sand cast bronze body and cap. 220°C high-temp teflon-jacketed sockered, crimped and heat shrunk cal connection to lead wire. Heavy duty 100% solid copper fixture entem — .115 wall thickness. Solid bronze canopy mount - secured by three brass masonry screws (not encluded) Can be mounted on retaining walls, fillars, and posts. The bottom center of the canopy into en be run through the back of the
Notes —			Plan Symbol:

- •CCH13CB: Requires S8 Wedge Base Lamp (not incl. 25w) Max. lamp rating 35 watts
- •Typical spacing 10' to 15'
- Refer to product installation sheet prior to installation

OPTIONS

- ☐ Mounting Canopy Unthreaded (CFM1CBS)
- ☐ Standard Mounting Stake (CMS1EM)
- ☐ Long Mounting Stake (CLMS1EM)
- ☐ Heavy Duty Mounting Stake (CHMS1CB)
- *NOTE: This is a threaded stake. To use with this fixture, purchase adapter (XCBPTLTA)

Unthreaded Stems:

- ☐ Replacement Stem (XCBPSTEMS______
- □Telescopic Stem (CWTRS_____)