Lighting Specification Sheet

Classic Large Mushroom Area/Path Light (CMU2CB)



Old world craftsmanship. . .tomorrow's technology® _ Date: _____ Project: _____ Fixture Type: _____ Quantity: _____ Specifier: Must operate lamp between 10.5-12.0 Drawing not to scale volts. Optimal range is 10.8 to 11.3. Check voltage with digital multi-meter. 304 knurled & slotted easy grip thumb screws. Extremely durable solid sand cast Highly reflective white 88-6-3-2 bronze body and cap. underside surface paint. 220°C high-temp teflon-jacketed socket. Reflected "no glare" light source. LED Retrofit: use CALED2-Internal drain stem. replaces halogen lamp CMU2CB: Wedge-base 25 watt Soldered, crimped and heat shrunk Krypton lamp light source. electrical connection to lead wire. 25,0" Heavy duty 100% solid copper fixture stem — .115 wall thickness. Keep stake top flush wlgrade. Large Talon Stake™ 8.5 #16-2@35' Tin coated marine grade No-Ox[®] wire.

Notes -

• CMU2CB: Requires S8 Wedge Base Lamp (not included, 25w) Max. lamp rating 35 watts

Coil leftover lead wire at base of fixture. This allows for future field adjustment

of fixture placement if required.

Bury wire at 6" depth.

- Typical spacing 10' to 15'
- Refer to product installation sheet prior to installation

OPTIONS

- Mounting Canopy Unthreaded (CFM1CBS)
- Standard Mounting Stake (CMS1EM)
- Large Talon Stake (CTSL1)(incl.)
- Long Mounting Stake (CLMS1EM)
- Heavy Duty Mounting Stake (CHMS1CB)
- *NOTE: This is a threaded stake. To use with this fixture, purchase adapter (XCBPTLTA).

Unthreaded Stems:

- Replacement Stem (XCBPSTEMS_____
- Telescopic Stem (CWTRS_____)

Plan Symbol: