Lighting Specification Sheet

Classic MR-11 Bullet Light (CBL5CB)



Old world craftsmanship...tomorrow's technology®

Project:	Date:
-	Quantity:
Specifier:	
Drawing not to scale	
Optimal voltage is 10.8 to 11.3 volts Check voltage with digital multi- meter.	Extremely durable solid sand-cast bronze body and copper shroud. 1.62"
MR-11 light source	, 35W maximum. 6.0"
High temperature corrosion-resista Install 90º to	olootrical connection to load wire
Set stake top flush with	Quick release feature allows stem insertion after setting stake in ground.
Pre-wired with 25 ft. #16/2 tin-coated, ma- rine-grade No-0x wire.	6.25"
Bury at 6" depth.	Compact backfill in 4" lifts.
Coil leftover lead wire at base of fixture. This allows for fu-	
ture field adjustment of fix- ture placement if required.	
Notes —	

- Requires MR-11 (not included)
- Max. lamp rating 35 watts
- •Use only covered MR-11 lamps

MOUNTING OPTIONS

- **★** Small Mounting Stake (CMS5CB)(incl)
- ☐ MR-11 Mounting Canopy (XCBPTMC2)

- Orient upwards unless protected from rain
- Refer to product installation sheet prior to installation

LENS OPTIONS

- □ Optical Spread Lens (COSL11)
- □ Optical Linear Spread Lens (COLL11)
- □ Optical Frosted Lens (COFL11)
- ☐ Hexcell Louver (CXL2)