




SOURCE
LIGHTING CO.

SSPK45

INTEGRATED LED 4.5 WATT SPOT LIGHT



PRODUCT SPECIFICATIONS

Fixture Material	Die cast Aluminium
Fixture Finish	Powder-coated bronze
Glass	Clear Glass
Optic	High temperature Japanese Acrylic
Cowl Material	Die cast Aluminium
Binning	3 Step MacAdam
Wiring	1 meter of 2 core 0.75mm ² rubber cable
Life Span	50,000 hours

LED Chip	Nichia
Power Consumption	4.5W
Input Voltage	12VAC, 50/60 Hz or 12VDC
Operating Temperature	from -4° to 149° F
Color Rendering Index	>85
Warranty	3 years against manufacturing defects
Agency Approval	CE, RoHS, ETL

Standard offering of fixture is 3000K and 35° Beam Spread. Other color temperatures (2700K, 4000K & 6000K), colors (red, green, blue) and beam spreads (10° and 65°) are available as a special order. Special orders require a minimum of 100 units and lead times for special orders are 8 weeks. Special orders require a 50% deposit on materials and any expedited freight charges will be the responsibility of the client.



Power (W)	Available color Temperatures	Luminous Flux			IP Rating	Available Beam Angles
		3000K	4000K	6000K		
4.5W	2700K 3000K 4000K 6000K RED GREEN BLUE	110lm/W	120lm/W	130lm/W	66	10° 35° 60°